



Design

The Metrotile Roman profile is designed to create the authentic look of the Mediterranean, with the additional benefits of steel roofing.

Metrotile Roman is a five tile, stone-coated panel pressed from a high grade of Aluzinc[®] coated steel and is available in a wide selection of colours to enhance any exterior colour scheme.

Installation

The Metrotile five tile panels can be interlocked either rightover left or left over right with the side laps of one small corrugation.

The panels are placed onto battens spacing 368 mm.

The downturned front edge and the upturned rear edge of eachtile provides a strong, weatherproof, overlapping and interlockingroof covering. Each panel is secured by 4 nails in the front-downturned edge into the side of the batten, positioned out of the water course.

Specifications

Minimum pitch	10°
Maximum pitch	90°
Size of tile - overall*	1280 x 415 mm [± 3 mm]
Size of tile - cover*	1220 x 368 mm
Gauge of steel	0,45 mm
Linear cover width*	1280 mm
Coverage*	0,449 m² (2,23 tiles per m²)
Weight per m ²	6,68 kg
Weight per tile	3,00 kg

* The measurements and the weight may vary slightly by the finish that is added to the accessory.

Packing

Pieces per pallet	320
Pallet composition	16 stacks of 20 pieces
Pallet dimensions	1400 x 1100 mm x 1050 mm